



GreenShield Inquiry Form

sales@basetek.com or 877-712-BASE (2273)



Company Quote to: _____

Project Reference _____

Contact _____

Equipment/Tag # _____

E-Mail _____

Phone _____

EQUIPMENT INFORMATION **SECTION 1**

- Pump Model/Size _____
- Motor Frame _____
- Distance Between Shafts _____
- Coupling Guard *** if inserts are required indicate quantity and size* _____
- Drawing provided _____
- Other _____
- Other _____

OVERALL DIMENSIONS **SECTION 2**

- Length _____
 - Width _____
 - Height ** _____
- ** As measured from bottom of GreenShield to bottom of limiting equipment mounting surface. DO NOT include grout allowance. Check all corners for tightest obstruction. GreenShield carries a tolerance of +/- 0.125"*

Mounting Options (choose one) **SECTION 3**

- Grouted
- Surface Mount (anchored with PoxyCove)
- Free Float
- Bury/Below Grade

Construction

- Solid
- Hollow Core
- Have BaseTek recommend (cost/weight)

Drip Pan

- Yes
- No

SECTION 4

Equipment Mounting Holes (choose one)

- 303SS (standard)
- 316SS
- C276
- Titanium

Material Spec (choose one)

- Zanite Plus
- Red Novolac
- Other

Mounting Block Options **SECTION 5**

- Standard Uniblock
- Standard block kit (4 blocks)
- Custom Risers

Grout Kit Installation Kit **SECTION 6**

- | | |
|------------------------------|------------------------------|
| <input type="checkbox"/> Yes | <input type="checkbox"/> Yes |
| <input type="checkbox"/> No | <input type="checkbox"/> No |

(enter inches)
Maximum epoxy grout depth

Notes: _____
